ELNA

■ Ordering Information

Please order by the multiples of the minimum order quantity (MOQ).

Aluminum Electrolytic Capacitors

Classification		Case Size φD×L (mm)	Quantity (PCS.)						
			Long lead		Forming lead		Taping (04 Type)	Taping (Chip Type)	
			(Q'ty/Bag)	MOQ/Box	(Q'ty/Bag)	MOQ/Box	MOQ/Box	MOQ/Reel	(Q'ty/Box)
Conductive Polymer Hybrid Aluminum Electrolytic Capacitors	Chip Type	φ5 to φ6.3	–	–	–	–	–	1,000	5,000
		φ8,φ10×10	–	–	–	–	–	500	2,000
		φ10×12.5	–	–	–	–	–	400	1,600
		φ10×16.5	–	–	–	–	–	250	1,000
		φ12.5×13.5	–	–	–	–	–	200	1,000
Chip Type		φ6.3	–	–	–	–	–	1,000	5,000
		φ8,φ10	–	–	–	–	–	500	2,000
		φ12.5×13.5	–	–	–	–	–	200	1,000
		φ16×16.5,φ18×16.5	–	–	–	–	–	125	250
		φ16×21.5,φ18×21.5	–	–	–	–	–	75	150
04 Type		φ10×12.5	200	1,000	200 (400)	1,000 (4,000)	500	–	–
		φ10×16	200	1,000	200	1,000	500	–	–
		φ10×20	200	1,000	200 (100)	1,000 (500)	500	–	–
		φ10×25 to 30	200	1,000	100 (200)	500 (1,000)	500	–	–
		φ12.5×15 to 20	100	1,000	100	1,000 (500)	500	–	–
		φ12.5×25	100	500 (1,000)	100	1,000 (500)	500	–	–
		φ12.5×30,35	100	500	200 (100)	2,000 (500)	500	–	–
		φ12.5×40	100	500 (100)	200 (100)	2,000 (500)	–	–	–
		φ16×16 to 25	100	500	100	1,000 (100)	–	–	–
		φ16×31.5 to 35.5	50	200 (400)	100	1,000 (100)	–	–	–
		φ16×40	50 (100)	100	100	800 (100)	–	–	–
		φ18×16	50	100	100	1,000 (100)	–	–	–
		φ18×20	50 (100)	100 (500)	100	1,000 (100)	–	–	–
		φ18×25	50 (100)	100 (400)	100	1,000 (100)	–	–	–
		φ18×31.5 to 35.5	50	100	100	1,000 (100)	–	–	–
		φ18×40	50	250 (100)	100	800 (100)	–	–	–

(Note) It may become the numerical value in ( ).

Electric Double Layer Capacitors

Type	Case size φD×L(mm)	Quantity (PCS.)						
		Long lead		Forming lead		Taping (04 Type)	Taping (Chip Type)	
		(Q'ty/Bag)	MOQ/Box	(Q'ty/Bag)	MOQ/Box	MOQ/Box	MOQ/Reel	(Q'ty/Box)
Cylindrical	φ6.3	200	2,000	200	2,000	2,000	–	–
	φ8×12	200	2,000	200	2,000	1,000	–	–
	φ8×20	200	1,000	200	1,000	1,000	–	–
	φ10×20 to 25	200	1,000	100	500	500	–	–
	φ10×30 to 35	200	1,000	100	500	500	–	–
	φ12.5×25	100	500	100	1,000	500	–	–
	φ12.5×35	100	500	200	2,000	–	–	–
	φ16×20 to 25	100	500	100	1,000	–	–	–
	φ16×31.5 to 35.5	50	200	100	1,000	–	–	–
	φ16×40	50	100	100	800	–	–	–
	φ18×40	50	250	100	800	–	–	–

NOTE : Design, Specifications are subject to change without notice.
It is recommended that you shall obtain technical specifications from ELNA to ensure that the component is suitable for your use.

CAT.No.2025/2026E